

TT-C-490 –Implementing alternatives through specifications



TECHNOLOGY DRIVEN. WARFIGHTER FOCUSED.

Tom Braswell, Fred Lafferman, John Kelley, Tom Considine, Chris Miller, William Lum, John A. Escarsega

ASETSDefense 2014 : Sustainable Surface Engineering

for Aerospace and Defense

November 18th 2014 Fort Myer, VA.

including suggestions for reducing	ompleting and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar DMB control number.	arters Services, Directorate for Infor	mation Operations and Reports	, 1215 Jefferson Davis I	Highway, Suite 1204, Arlington		
1. REPORT DATE 18 NOV 2014		2. REPORT TYPE		3. DATES COVE 00-00-2014	red to 00-00-2014		
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER			
TT-C-490 -Implementing alternatives through specifications				5b. GRANT NUMBER			
			5c. PROGRAM ELEMENT NUMBER				
6. AUTHOR(S)				5d. PROJECT NUMBER			
			5e. TASK NUMBER				
				5f. WORK UNIT NUMBER			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Army Research Laboratory,2800 Powder Mill Road,Adelphi,MD,20783 8. PERFORMING ORGANIZATION REPORT NUMBER							
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)			
				11. SPONSOR/M NUMBER(S)	ONITOR'S REPORT		
12. DISTRIBUTION/AVAIL Approved for publ	LABILITY STATEMENT ic release; distributi	ion unlimited					
13. SUPPLEMENTARY NO ASETSDefense 201 Myer, VA.	otes 14: Sustainable Surf	ace Engineering for	Aerospace and I	Defense, 18-20) Nov 2014, Fort		
14. ABSTRACT							
15. SUBJECT TERMS							
16. SECURITY CLASSIFICATION OF: 17. LIMITA				18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON		
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	24	RESTUNSIBLE PERSUN		

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and

Report Documentation Page

Form Approved OMB No. 0704-0188



Outline



➤ 1. Background and Motivation for TT-C-490

≥2. Strategy for Over-Arching Specifications

➤ 3. Details of the Specification

>4. Closing Comments



What is TT-C-490?



Prior to 2013, TT-C-490 was "Chemical Conversion Coatings and Pretreatments for <u>Ferrous Surfaces</u> (Base for Organic Coatings)"



Existing Pretreatments for CARC Coating System TT-C-490E



Prior to 2013, TT-C-490 was "Chemical Conversion Coatings and Pretreatments for Ferrous Surfaces (Base for Organic Coatings)"

INCH-POUND

TT-C-490E July 22, 2002 __ SUPERSEDING TT-C-490D March 31, 1993

FEDERAL SPECIFICATION

CHEMICAL CONVERSION COATINGS AND PRETREATMENTS FOR FERROUS SURFACES (BASE FOR ORGANIC COATINGS)

This specification was approved by the Assistant Administrator Office of Federal Supply and Services, General Services Administration, for the use by all Federal Agencies.

- 1. SCOPE AND CLASSIFICATION
- 1.1 Scope. This specification covers cleaning, surface conditioning for crystal refinement and pretreatment by chemical conversion of ferrous metals and zinc/zinc alloy coated metals. The application of chemical conversion and pretreatment coatings provides uniformly textured substrates for receiving and retaining paint, lacquer, etc. In addition, this specification covers suitable cleaning processes for nonferrous surfaces (see 6.1, 6.1.2).
- 1.2 <u>Classification</u>. This specification covers the following cleaning methods and surface preparation processes:
- 1.2.1 Surface cleaning. Surface cleaning should be by any of the following methods as specified (see 6.4):

Method I Mechanical or abrasive cleaning.

Method II Solvent cleaning by immersion, spray or vapor.

Method III Hot alkaline cleaning by immersion, spray or electrolytic methods.

Method IV Emulsion with or without added water.

Method V Alkaline derusting

Method VI Phosphoric acid (alcohol, detergent or solvent type with detergent).

- 1.2.1.1 Ozone depleting chemicals. The cleaning material should not contain any chemical, which is classified in the Clean Air Act Amendments of 1990 as a Class I or Class II ozone depleting substance.
- 1.2.2 Conversion coatings and pretreatments. Chemical conversion and pretreatment coatings should be of the following types as specified (see 6.4).

Type I Zinc phosphate spray application (150 mg/ft² min - 500 mg/ft² max)

Zinc phosphate immersion or dip application (300 mg/ft² min - 500 mg/ft² max)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Director, U.S. Army Research Laberatory, Weapons and Materials Research Directorate, ATTN: AMSRL-WM-M, Aberdeen Proving Ground, MD 21005-5069 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A AREA MFFP

- Pretreatments specific for ferrous substrates
- Specifies either zinc phosphate conversion coating or wash primer conforming to DOD-P-15328 or MIL-C-8514
- Wash primers contain hexavalent chromium
 - Also high in VOCs and contain HAPs
 - Only pretreatment allowed for multimetal application
- Zinc phosphate is either applied by immersion or spray in a contained area



Major Gaps in TT-C-490E Pretreatments

- ARL
- Other than DOD-P-15328 & MIL-C-8514, there was no other pretreatment approved for multi-metal application
 - No approved alternatives to wash primer
- Most users do not have facilities large enough to apply zinc phosphate to structures and hulls
- Material compatibility issues (heat, acids, etc)
 - Hydrogen embrittlement risks perceived with WP and Phos
- No avenue to evaluate, approve, and adopt new technologies
- Direct-to-metal is not approved for CARC
 - Limited exemption by waiver



Motivation to update TT-C-490



- TT-C-490 became outdated and used beyond original scope
- Restrictive language limits process improvements and prevents innovation
 - Lock-step procedures dictate material selections
 - Proven technologies are available and being used in commercial industries
- John J. Young Jr., The Office of the Undersecretary of Defense, memo (April 8, 2009) mandating reduction in chrome has led to elimination of TT-C-490 Type III (DoD-P-15328) on most new contracts
 - Impending cancellation of Type III DoD-P-15328
- Technologies demonstrated for military applications (e.g.: ESTCP WP-200906) have no avenue other than waivers to use materials and processes outside specification
- Engineering drawings specific to TT-C-490 process have forced OEM's to get PM approvals on materials not yet evaluated by ARL





Why TT-C- 490?



TT-C-490E, "Chemical Conversion Coatings and Pretreatments for Ferrous Surfaces (Base for Organic Coatings)"




- Overarching document referenced in tens of thousands of military specifications and drawings
- The definitive reference for engineers to specify cleaning and pretreatment of ferrous materials
 - Often used improperly for cleaning non-ferrous metals
- Major gaps existed between the technologies permitted in TT-C-490E and what is available today
 - Prohibited use of chromated wash primer and eventual cancellation leaves technology gap for large components and multi-metal assemblies
- TT-C-490 is used by all services and OEMs for finishing metal



Revision Timeline







ARL TT-C-490F Team



Team Member	Contribution
Thomas Braswell	TT-C-490F Team Lead
Fred Lafferman	Coatings Technical Lead
Bernie Hart (retired)	Specification and Standards
William Lum	Specification Coordinator
Thomas Considine	Corrosion Testing Standards
Christopher Miller	Subject Matter Expert TT-C-490E
John Kelley	Corrosion Team Facilitator



RDECOM Significant Changes in TT-C-490F



- TT-C-490F will require Objective Quality Evidence (OQE)
 - Continuous monitoring... "Tell me, show me, prove it"
 - Requires the use of certifiable process checks (ISO 9001/17025) to demonstrate competencies
 - Replaces "old" quality system which did not adequately control ongoing quality production
 - Government had insufficient resources to follow-up
 - No more <u>"set and forget"</u> production lines
 - Applies to both legacy and new systems
 - New systems also require qualification through QPD
- TT-C-490F bolsters the quality of legacy zinc phosphate systems while maintaining integrity of the original processes including optional on-site inspection
- Incorporation of non-ferrous substrates embraces new technologies
- Enables the use of new approved technologies without the need for negotiating within contract
- ARL steward of QPD



Impact of TT-C-490F




What does this all mean to DOD and its contractors?

- TT-C-490F augments requirements in MIL-DTL-53072
- More flexibility in terms of pretreatment choices
 - First Fed specification to encourage the use of new technologies for multiple metal substrates
- New TT-C-490 technologies can be applied through Engineer
 Change Notice (ECN) without changes to main drawings (drawing changes = \$\$\$\$)
- Greener technologies
 - Significant step towards elimination of Cr⁶⁺, VOC's and HAP's
 - Reduced energy costs for operating pretreatment lines
 - Reduced wastes (little or no sludge removal/maintenance)
- In some cases, vastly better performance (zinc-rich)
- Applied program of quality assurance OQE
- ARL stewardship
 - Provides QPD for approved materials
 - Formal path for evaluating new materials and processes
 - Encourages innovation



Impact of TT-C-490F








Impact of TT-C-490F ARL



Example of Potential Cost Savings

	Zinc Phosphate 125°F (52°C)	Iron Phosphate 125°F (52°C)	Advanced Pretreatment 70°F (21°C)
Chemical Cost	\$100	\$100	\$100
Heating Energy	\$100	\$100	\$70
Electric Energy	\$100	\$86	\$71
Rinsing Water	\$100	\$100	\$40
Waste Disposal	\$100	\$35	\$17
Maintenance	\$100	\$25	\$15
	\$600	\$446	\$313





Impact of TT-C-490F ARL



Foundation for MIL-DTL-53072

- Chemical Agent Resistant Coating (CARC) consists of four distinct steps:
 - Cleaning and Preparation of Substrate (TT-C-490)
 - Pretreatment (TT-C-490)

Priming

Top-coating












Over-Arching Specifications







Qualification of New Technology



- New Types that require qualification and inclusion in Qualified Products Database:
 - Type III Organic pretreatments (chromate free)
 - Type IV Inorganic pretreatments (silanes, zirconates, etc)
 - Type VIII Metal-rich coatings for abrasive blasted surfaces
- Zinc phosphate, iron phosphate and current wash primers are legacy systems and do not require TT-C-490 QPD
- Statements of composition (full disclosure) and process requirements required for qualification
- QPD will be based upon Type, Class, and Cleaning Method
- Performance criteria established in specification and must be compatible with CARC primers
- QPD is transition from specification to implementation



Qualification of New Technology



1

- Complete all required testing
 - Pass all requirements for TT-C-490F
 - (Type IV Inorganic Pretreatment)

2

- Manufacturer submits Letter of Intent
 - Specify Type and Class
 - Provide full disclosure

3

- TT-C-490F Team Review of documentation
 - Approved and placed on QPD



490F: Answers in regard to Transition Questions



- Expected questions from users:
 - What is the transition method to implement new pretreatment technologies?
 - Approval to TT-C-490F requirements
 - ARL initiates a formal QPD program
 - Legacy products not affected
 - Will it effect government drawings and contracts?
 - No effects on existing drawings and contracts
 - Can use ECNs to access new technologies
 - Enables new technologies to be used in future contracts
 - Will the new technologies cost more?
 - Generally, no
 - Enhanced performance products may increase costs
 - i.e.: zinc metal



Summary of TT-C-490F ARL

- Overarching document referenced in tens of thousands of military specifications and drawings
- Requires continuous monitoring to provide objective quality evidence (OQE).
 - Bolsters quality of legacy systems like phosphate
- Encompasses both ferrous and non-ferrous substrates
- ARL stewardship provides formal process for evaluating and approving new materials for QPD
- Expedites implementation of new approved technologies by providing a QPD
 - No need for negotiating within contract
 - Implementation strategy for WP200906 and TMR-12-01



Current Types in 490F ARL



- Type I Zinc phosphate.
- Type II Aqueous iron phosphate.
- Type III Organic pretreatment.
- Type IV Inorganic pretreatment.
- Type V Medium weight zinc phosphate.
- Type VI MIL-DTL-5541, Chemical
- Conversion Coatings on Aluminum and
- Aluminum Alloys.
- Type VII Anodic coating and electrolytic passivation.
- Type VIII Metal-rich coating for abrasive blasted surfaces



Closing Comments



- Specifications are just one link to many elements to support implementation and use of new technologies.
- ❖Posture is to reduce the number of "types" in specification to ensure only top level performance.
- Request and Mandate OEMs, Vendors and DOD do not restrict or isolate a particular technology.....reference the specification and select what works best for each end-user.



Stakeholders/Contributors



TT-C-490F Reconstruction Contributors				
Contributor	Organization			
John Escarsega	US Army Research Laboratory, MMSD-CARC Commodity Manager, Signature approving Authority			
William Lum	US Army Research Laboratory, MMSD-Coatings Team, APG, MD 21005			
Fred Lafferman	US Army Research Laboratory, MMSD-Corrosion Team, APG, MD 21005			
Chris Miller	US Army Research Laboratory, MMSD-Corrosion Team, APG, MD 21005			
Brian Plazankis	US Army Research Laboratory, MMSD-Corrosion Team, APG, MD 21005			
Tom Considine	US Army Research Laboratory, MMSD-Corrosion Team, APG, MD 21005			
Tom Braswell	US Army Research Laboratory, MMSD-Corrosion Team, APG, MD 21005			
Scott Grendal	US Army Research Laboratory, APG, MD 21005			
Jonathan Montgomery	US Army Research Laboratory, APG, MD 21005			
Bernard Hart (retired)	US Army Research Laboratory, MMSD-Coatings Team, APG, MD 21005			
Jack Kelley	US Army Research Laboratory, MMSD-Corrosion Team, APG, MD 21005			
Gary Nelson	Chemetall Inc			
Randall Brady	Deft Coatings			
Chuck Ray	Deft Coatings			
Mike Berger	Henkel			
George Newton	Henkel			
Pat Scalera	Henkel			
John Mort	Hentzen Coatings			
Terry Tuttle	Hentzen Coatings			
Wes Prince	Impregion Corp.			
Amy Fowler	Naval Air Warfare Center, Patuxant River, MD			
Randy Terrill	NCP Coatings			
Matt Flory	Sherwin Williams			
Nabil Zaki	Surtec Inc			
Bernie Tucker	Tucker Liquid Ind. Coatings			
Joe Menke	Corrosion Engineer, RIA			
Carl Handsy (retired)	TARDEC			
Jeff Adams	AMZ Corporation			



Contacts for TT-C-490F



Contacts	Telephone	Email
Thomas Braswell	410-306-0935	Thomas.braswell2.civ@mail,mil
Fred Lafferman	410-306-1520	fred.lafferman.civ@mail.mil
John Escarsega	410-306-0693	john.a.escarsega.civ@mail.mil
William Lum	410-306-0706	william.s.lum.civ@mail.mil
Thomas Considine	410-306-2564	thomas.a.considine.ctr@mail.mil
Christopher Miller	410-306-0849	christopher.e.miller44.civ@mail.mil
John Kelley	410-306-0837	John.v.kelley8.civ@mail.mil



Questions







TECHNOLOGY DRIVEN. WARFIGHTER FOCUSED.